THE BEST CASE SCENARIO IN DRILLING OPERATIONS


DESIGNED WITH SAFETY IN MIND

Premiere's casing running tool (PRT™) is the result of cutting edge engineering and field tested standards. The PRT™ features a compact design, rugged construction, and the versatility to run various pipe sizes and weights without compromising performance. Designed with full string handling capabilities (simultaneously pickup, drill, run, ream, rotate, and reciprocate) for casing running operations, the PRT™ decreases the chances of sticking pipe downhole. The PRT™ has the ability to fill up and reciprocate the pipe during critical make up or break out procedures. Integrated with a fail safe True-Lock design, the PRT™ virtually eliminates the risk of dropping pipe.



Casing Running Package

- Eliminates the need for an elevator, tongs, bails, and stabber
- Inherently safer than running conventional casing
- Solid forged body with internally plumbed hydraulic hoses and fittings so as not to be damaged while in use



Fail Safe Wedge Grip Slip Design

- 100% grip on pipe, even if hydraulic pressure is lost
- Compatible with casing sizes ranging from 4 1/2" (114.3 mm) to 30" (762 mm)



High Speed Swivel

- Stores energy to achieve up to 230 RPM
- Rotates for extended hours at maximum torque promoting optimal casing drilling operations



Handles With Ease

- Quick Connect System provides significantly faster rig-up/rigdown times (45 minutes on average)
- Compact design allows for easier handling
- Approximately 30-50% lighter than the competition



Remotely Operated Control Panel

- Controlled by a single person through a user friendly, remotely operated control panel
- Four-tier safety design significantly reduces the risk of dropping pipe





Interlock System & Slip Position Indicator

- Greatly reduces the risk of dropped pipe
- Ensures slips are set on casing and not collar

THE BEST CASE SCENARIO IN DRILLING OPERATIONS

PREMIERE DESIGNED

Since the PRT™ was designed in-house, Premiere has the ability to instantly make design changes to better suit the needs of our customers. Each tool is tested and retested so that we may ensure a safe and efficient product that stands up to the rigors of today's oilfield. The PRT™ is truly years ahead of competing CRTs.

API 8C SPECIFICATIONS

Designed and manufactured to meet and exceed the API 8C specifications, the PRT™ can handle more weight and rotational torque, allowing us to perform more critical movements without having to stop the casing run.

Rotational torque remains consistent regardless of any increases in string weight or pump pressure.

350 TON PRT SPECIFICATIONS

	Standard	Metric
Top Drive Connection	As Per Customer Request	As Per Customer Request
Max Hoisting Capacity	350 Tons	317 Metric Tons
Casing Sizes	4 1/2" to 30"	114.3 mm to 762 mm
Max Rotating Speed	230 RPMs	230 RPMs
Max Pressure Rating	10,000 psi	68.9 MPa
Max Torque	50,000 ft-lbs	67,790 Newton Meters
Length (with fill-up tool)	99"	2.515 Meters
Width	21.75″	.55 Meters
Weight (dressed)	5,693 lbs	2,582 kgs

